

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Light Loss Factor	Wattage
	AL-1	9	Lithonia Lighting	DSX1 LED P2 30K T3M MVOLT HS	DSX1 Area Light Type 3 Distribution w/ house side shield Pole Mounted @ 20'-0" AFG on a single head pole @ 90°	0.9	70
	AL-3	4	Lithonia Lighting	DSX1 LED P2 30K T4M MVOLT	DSX1 Area Light Type 4 Distribution Pole Mounted @ 20'-0" AFG on a double head pole @ 180°	0.9	140
	DP-1	14	Lumenpulse	PURXXX VOLT CSL S40 30K CRI70 3 FINISH DIM XX XX	Pure Series - Decorative Pedestrian Scale Pole Type 3 Beam Mounted @ 12'-0" AFG	0.9	31
	DP-1b	2	Lumenpulse	PURXXX VOLT CSL S40 30K CRI70 3BLS FINISH DIM XX XX	Pure Series - Decorative Pedestrian Scale Pole Type 3 Beam w/ Back Side Shield Mounted @ 12'-0" AFG	0.9	31
	W1	8	Zaneen	L9W603 30K FINISH XX	One Surface Mounted Direct Indirect	0.9	29
	W2	6	Spectrum Lighting	WS1210GV 15L 30K DRIVER TF2 *WALL MOUNT* FINISH FINISH WLKA	Warehouse Shade Series - Wall mounted *advise mounting arm* - 12In Dia.	0.9	10
	W5	4	Spectrum Lighting	WS2015GV 27L 30K DRIVER TF2 *WALL MOUNT* FINISH FINISH WLKA	Warehouse Shade Series - Wall mounted *advise mounting arm* - 20In Dia.	0.9	18
	W6	3	Hydrel	Pine P1 80CRI 30K 120 20DEG FLC	Pine Flag Spot Light	0.9	33.1