

Site Plans

Issued for	Local Approvals
Date Issued	November 20, 2018
Latest Issue	November 20, 2018

Proposed Urgent Care Facility

296 Old Oak Street
Pembroke, MA

Owner/Applicant

D & C Real Estate Trust CTS
Fiduciary LLC Trustee
Turtle Rock, LLC
231 Willow Street
Yarmouth Port, MA 02675

Assessor's Map: G15
Lot: 35



Sheet Index		
No.	Drawing Title	Latest Issue
C-1	Legend and General Notes	November 15, 2018
C-2	Locus Map	November 15, 2018
C-3	Layout and Materials Plan	November 15, 2018
C-4	Grading, Drainage & Erosion Control Plan	November 15, 2018
C-5	Utility Plan	November 15, 2018
C-6.1	Site Details 1	November 15, 2018
C-6.2	Site Details 2	November 15, 2018
L-1	Planting Plan	November 15, 2018
L-2	Planting Details	November 15, 2018

Reference Drawings		
No.	Drawing Title	Latest Issue
	Existing Conditions Plan	November 14, 2018
A101	Building A Floor Plan	November 2, 2018
A201	Building Elevations	November 13, 2018
	Site Lighting Plan and Details	November 20, 2018



vhb.com

101 Walnut Street
PO Box 9151
Watertown, MA 02471
617.924.1770

Land Surveyor
Stenbeck & Taylor
844 Webster Street #3
Marshfield, MA 02050
781.834.8591

Site Lighting
TECHLIGHT
2707 Satsuma
Dallas, TX 75229

PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I,
TOWN CLERK OF THE TOWN OF PEMBROKE, MA
HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.



Kenneth S. Staffier
11/20/2018



101 Walnut Street
PO Box 9151
Watertown, MA 02471
617.924.1770

Legend

Exist.	Prop.		Exist.	Prop.	
		PROPERTY LINE			CONCRETE
		PROJECT LIMIT LINE			HEAVY DUTY PAVEMENT
		RIGHT-OF-WAY/PROPERTY LINE			BUILDINGS
		EASEMENT			RIPRAP
		BUILDING SETBACK			CONSTRUCTION EXIT
		PARKING SETBACK	27.35 TC x	27.35 TC x	TOP OF CURB ELEVATION
		BASELINE	26.85 BC x	26.85 BC x	BOTTOM OF CURB ELEVATION
		CONSTRUCTION LAYOUT	132.75 x	132.75 x	SPOT ELEVATION
		ZONING LINE	45.0 TW x	45.0 TW x	TOP & BOTTOM OF WALL ELEVATION
		TOWN LINE	38.5 BW	38.5 BW	BORING LOCATION
		LIMIT OF DISTURBANCE			TEST PIT LOCATION
		WETLAND LINE WITH FLAG			MONITORING WELL
		FLOODPLAIN			UNDERDRAIN
		BORDERING LAND SUBJECT TO FLOODING			DRAIN
		WETLAND BUFFER ZONE			ROOF DRAIN
		NO DISTURB ZONE			SEWER
		200' RIVERFRONT AREA			FORCE MAIN
		GRAVEL ROAD			OVERHEAD WIRE
		EDGE OF PAVEMENT			WATER
		BITUMINOUS BERM			FIRE PROTECTION
		BITUMINOUS CURB			DOMESTIC WATER
		CONCRETE CURB			GAS
		CURB AND GUTTER			ELECTRIC
		EXTRUDED CONCRETE CURB			STEAM
		MONOLITHIC CONCRETE CURB			TELEPHONE
		PRECAST CONC. CURB			FIRE ALARM
		SLOPED GRAN. EDGING			CABLE TV
		VERT. GRAN. CURB			CATCH BASIN CONCENTRIC
		LIMIT OF CURB TYPE			CATCH BASIN ECCENTRIC
		SAWCUT			DOUBLE CATCH BASIN CONCENTRIC
		BUILDING			DOUBLE CATCH BASIN ECCENTRIC
		BUILDING ENTRANCE			GUTTER INLET
		LOADING DOCK			DRAIN MANHOLE CONCENTRIC
		BOLLARD			DRAIN MANHOLE ECCENTRIC
		DUMPSTER PAD			TRENCH DRAIN
		SIGN			PLUG OR CAP
		DOUBLE SIGN			CLEANOUT
		STEEL GUARDRAIL			FLARED END SECTION
		WOOD GUARDRAIL			HEADWALL
		PATH			SEWER MANHOLE CONCENTRIC
		TREE LINE			SEWER MANHOLE ECCENTRIC
		WIRE FENCE			CURB STOP & BOX
		FENCE			WATER VALVE & BOX
		STOCKADE FENCE			TAPPING SLEEVE, VALVE & BOX
		STONE WALL			SIAMESE CONNECTION
		RETAINING WALL			FIRE HYDRANT
		STREAM / POND / WATER COURSE			WATER METER
		DETENTION BASIN			POST INDICATOR VALVE
		HAY BALES			WATER WELL
		SILT FENCE			GAS GATE
		SILT SOCK / STRAW WATTLE			GAS METER
		MINOR CONTOUR			ELECTRIC MANHOLE
		MAJOR CONTOUR			ELECTRIC METER
		PARKING COUNT			LIGHT POLE
		COMPACT PARKING STALLS			TELEPHONE MANHOLE
		DOUBLE YELLOW LINE			TRANSFORMER PAD
		STOP LINE			UTILITY POLE
		CROSSWALK			GUY POLE
		ACCESSIBLE CURB RAMP			GUY WIRE & ANCHOR
		ACCESSIBLE PARKING			HAND HOLE
		VAN-ACCESSIBLE PARKING			PULL BOX
		MATCHLINE			MATCHLINE

Abbreviations

General	
ABAN	ABANDON
ACR	ACCESSIBLE CURB RAMP
ADJ	ADJUST
APPROX	APPROXIMATE
BIT	BITUMINOUS
B5	BOTTOM OF SLOPE
BWLL	BROKEN WHITE LANE LINE
CONC	CONCRETE
DYCL	DOUBLE YELLOW CENTER LINE
EL	ELEVATION
ELEV	ELEVATION
EX	EXISTING
FDN	FOUNDATION
FFE	FIRST FLOOR ELEVATION
GRAN	GRANITE
GTD	GRADE TO DRAIN
LA	LANDSCAPE AREA
LOD	LIMIT OF DISTURBANCE
MAX	MAXIMUM
MIN	MINIMUM
NIC	NOT IN CONTRACT
NTS	NOT TO SCALE
PERF	PERFORATED
PROP	PROPOSED
REM	REMOVE
RET	RETAIN
R&D	REMOVE AND DISPOSE
R&R	REMOVE AND RESET
SWEL	SOLID WHITE EDGE LINE
SWLL	SOLID WHITE LANE LINE
TS	TOP OF SLOPE
TYP	TYPICAL
Utility	
CB	CATCH BASIN
CMP	CORRUGATED METAL PIPE
CO	CLEANOUT
DCB	DOUBLE CATCH BASIN
DMH	DRAIN MANHOLE
CIP	CAST IRON PIPE
COND	CONDUIT
DIP	DUCTILE IRON PIPE
FES	FLARED END SECTION
FM	FORCE MAIN
F&G	FRAME AND GRATE
F&C	FRAME AND COVER
GI	GUTTER INLET
GT	GREASE TRAP
HDPE	HIGH DENSITY POLYETHYLENE PIPE
HH	HANDHOLE
HW	HEADWALL
HYD	HYDRANT
INV	INVERT ELEVATION
I=	INVERT ELEVATION
LP	LIGHT POLE
MES	METAL END SECTION
PIV	POST INDICATOR VALVE
PWW	PAVED WATER WAY
PVC	POLYVINYLCHLORIDE PIPE
RCP	REINFORCED CONCRETE PIPE
R=	RIM ELEVATION
RIM=	RIM ELEVATION
SMH	SEWER MANHOLE
TSV	TAPPING SLEEVE, VALVE AND BOX
UG	UNDERGROUND
UP	UTILITY POLE

Notes

General

1. CONTRACTOR SHALL NOTIFY "DIG-SAFE" (1-888-344-7233) AT LEAST 72 HOURS BEFORE EXCAVATING.
2. CONTRACTOR SHALL BE RESPONSIBLE FOR SITE SECURITY AND JOB SAFETY. CONSTRUCTION ACTIVITIES SHALL BE IN ACCORDANCE WITH OSHA STANDARDS AND LOCAL REQUIREMENTS.
3. ACCESSIBLE ROUTES, PARKING SPACES, RAMPS, SIDEWALKS AND WALKWAYS SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE FEDERAL AMERICANS WITH DISABILITIES ACT AND WITH STATE AND LOCAL LAWS AND REGULATIONS (WHICHEVER ARE MORE STRINGENT).
4. AREAS DISTURBED DURING CONSTRUCTION AND NOT RESTORED WITH IMPERVIOUS SURFACES (BUILDINGS, PAVEMENTS, WALKS, ETC) SHALL RECEIVE SIX (6) INCHES LOAM AND SEED.
5. WITHIN THE LIMITS OF THE BUILDING FOOTPRINT, THE CONTRACTOR SHALL PERFORM EARTHWORK OPERATIONS REQUIRED UP TO SUBGRADE ELEVATIONS.
6. WORK WITHIN THE LOCAL RIGHTS-OF-WAY SHALL CONFORM TO LOCAL MUNICIPAL STANDARDS. WORK WITHIN STATE RIGHTS-OF-WAY SHALL CONFORM TO THE LATEST EDITION OF THE STATE HIGHWAY DEPARTMENTS STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES.
7. UPON AWARD OF CONTRACT, CONTRACTOR SHALL MAKE NECESSARY CONSTRUCTION NOTIFICATIONS AND APPLY FOR AND OBTAIN NECESSARY PERMITS, PAY FEES, AND POST BONDS ASSOCIATED WITH THE WORK INDICATED ON THE DRAWINGS, IN THE SPECIFICATIONS, AND IN THE CONTRACT DOCUMENTS. DO NOT CLOSE OR OBSTRUCT ROADWAYS, SIDEWALKS, AND FIRE HYDRANTS, WITHOUT APPROPRIATE PERMITS.
8. TRAFFIC SIGNAGE AND PAVEMENT MARKINGS SHALL CONFORM TO THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.
9. AREAS OUTSIDE THE LIMITS OF PROPOSED WORK DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY THE CONTRACTOR TO THEIR ORIGINAL CONDITION AT THE CONTRACTOR'S EXPENSE.
10. IN THE EVENT THAT SUSPECTED CONTAMINATED SOIL, GROUNDWATER, AND OTHER MEDIA ARE ENCOUNTERED DURING EXCAVATION AND CONSTRUCTION ACTIVITIES BASED ON VISUAL, OLFACORY, OR OTHER EVIDENCE, THE CONTRACTOR SHALL STOP WORK IN THE VICINITY OF THE SUSPECT MATERIAL TO AVOID FURTHER SPREADING OF THE MATERIAL, AND SHALL NOTIFY THE OWNER IMMEDIATELY SO THAT THE APPROPRIATE TESTING AND SUBSEQUENT ACTION CAN BE TAKEN.
11. CONTRACTOR SHALL PREVENT DUST, SEDIMENT, AND DEBRIS FROM EXITING THE SITE AND SHALL BE RESPONSIBLE FOR CLEANUP, REPAIRS AND CORRECTIVE ACTION IF SUCH OCCURS.
12. DAMAGE RESULTING FROM CONSTRUCTION LOADS SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO OWNER.
13. CONTRACTOR SHALL CONTROL STORMWATER RUNOFF DURING CONSTRUCTION TO PREVENT ADVERSE IMPACTS TO OFF SITE AREAS, AND SHALL BE RESPONSIBLE TO REPAIR RESULTING DAMAGES, IF ANY, NO COST TO OWNER.

Utilities

1. THE LOCATIONS, SIZES, AND TYPES OF EXISTING UTILITIES ARE SHOWN AS AN APPROXIMATE REPRESENTATION ONLY. THE OWNER OR ITS REPRESENTATIVE(S) HAVE NOT INDEPENDENTLY VERIFIED THIS INFORMATION AS SHOWN ON THE PLANS. THE UTILITY INFORMATION SHOWN DOES NOT GUARANTEE THE ACTUAL EXISTENCE, SERVICEABILITY, OR OTHER DATA CONCERNING THE UTILITIES, NOR DOES IT GUARANTEE AGAINST THE POSSIBILITY THAT ADDITIONAL UTILITIES MAY BE PRESENT THAT ARE NOT SHOWN ON THE PLANS. PRIOR TO ORDERING MATERIALS AND BEGINNING CONSTRUCTION, THE CONTRACTOR SHALL VERIFY AND DETERMINE THE EXACT LOCATIONS, SIZES, AND ELEVATIONS OF THE POINTS OF CONNECTIONS TO EXISTING UTILITIES AND, SHALL CONFIRM THAT THERE ARE NO INTERFERENCES WITH EXISTING UTILITIES AND THE PROPOSED UTILITY ROUTES, INCLUDING ROUTES WITHIN THE PUBLIC RIGHTS OF WAY.
2. WHERE AN EXISTING UTILITY IS FOUND TO CONFLICT WITH THE PROPOSED WORK, OR EXISTING CONDITIONS DIFFER FROM THOSE SHOWN SUCH THAT THE WORK CANNOT BE COMPLETED AS INTENDED, THE LOCATION, ELEVATION, AND SIZE OF THE UTILITY SHALL BE ACCURATELY DETERMINED WITHOUT DELAY BY THE CONTRACTOR, AND THE INFORMATION FURNISHED IN WRITING TO THE OWNER'S REPRESENTATIVE FOR THE RESOLUTION OF THE CONFLICT AND CONTRACTOR'S FAILURE TO NOTIFY PRIOR TO PERFORMING ADDITIONAL WORK RELEASES OWNER FROM OBLIGATIONS FOR ADDITIONAL PAYMENTS WHICH OTHERWISE MAY BE WARRANTED TO RESOLVE THE CONFLICT.
3. SET CATCH BASIN RIMS, AND INVERTS OF SEWERS, DRAINS, AND DITCHES IN ACCORDANCE WITH ELEVATIONS ON THE GRADING AND UTILITY PLANS.
4. RIM ELEVATIONS FOR DRAIN AND SEWER MANHOLES, WATER VALVE COVERS, GAS GATES, ELECTRIC AND TELEPHONE PULL BOXES, AND MANHOLES, AND OTHER SUCH ITEMS, ARE APPROXIMATE AND SHALL BE SET/RESET AS FOLLOWS:
 - A. PAVEMENTS AND CONCRETE SURFACES: FLUSH
 - B. ALL SURFACES ALONG ACCESSIBLE ROUTES: FLUSH
 - C. LANDSCAPE, LOAM AND SEED, AND OTHER EARTH SURFACE AREAS: ONE INCH ABOVE SURROUNDING AREA AND TAPER EACH TO THE RIM ELEVATION.
5. THE LOCATION, SIZE, DEPTH, AND SPECIFICATIONS FOR CONSTRUCTION OF PROPOSED PRIVATE UTILITY SERVICES SHALL BE INSTALLED ACCORDING TO THE REQUIREMENTS PROVIDED BY, AND APPROVED BY, THE RESPECTIVE UTILITY COMPANY (GAS, TELEPHONE, ELECTRIC, FIRE ALARM, ETC.). FINAL DESIGN LOADS AND LOCATIONS TO BE COORDINATED WITH OWNER AND ARCHITECT.
6. CONTRACTOR SHALL MAKE ARRANGEMENTS FOR AND SHALL BE RESPONSIBLE FOR PAYING FEES FOR POLE RELOCATION AND FOR THE ALTERATION AND ADJUSTMENT OF GAS, ELECTRIC, TELEPHONE, FIRE ALARM, AND ANY OTHER PRIVATE UTILITIES, WHETHER WORK IS PERFORMED BY CONTRACTOR OR BY THE UTILITIES COMPANY.
7. UTILITY PIPE MATERIALS SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED ON THE PLAN:

Layout and Materials

1. DIMENSIONS ARE FROM THE FACE OF CURB, FACE OF BUILDING, FACE OF WALL, AND CENTER LINE OF PAVEMENT MARKINGS, UNLESS OTHERWISE NOTED.
2. CURB RADII ARE 3 FEET UNLESS OTHERWISE NOTED.
3. CURBING SHALL BE PCC (PRECAST CONCRETE CURB) WITHIN THE SITE UNLESS OTHERWISE INDICATED ON THE PLANS.
4. SEE ARCHITECTURAL DRAWINGS FOR EXACT BUILDING DIMENSIONS AND DETAILS CONTIGUOUS TO THE BUILDING, INCLUDING SIDEWALKS, RAMPS, BUILDING ENTRANCES, STAIRWAYS, UTILITY PENETRATIONS, CONCRETE DOOR PADS, COMPACTOR PAD, LOADING DOCKS, BOLLARDS, ETC.
5. PROPOSED BOUNDS AND ANY EXISTING PROPERTY LINE MONUMENTATION DISTURBED DURING CONSTRUCTION SHALL BE SET OR RESET BY A PROFESSIONAL LICENSED SURVEYOR.
6. PRIOR TO START OF CONSTRUCTION, CONTRACTOR SHALL VERIFY EXISTING PAVEMENT ELEVATIONS AT INTERFACE WITH PROPOSED PAVEMENTS, AND EXISTING GROUND ELEVATIONS ADJACENT TO DRAINAGE OUTLETS TO ASSURE PROPER TRANSITIONS BETWEEN EXISTING AND PROPOSED FACILITIES.

Demolition

1. CONTRACTOR SHALL REMOVE AND DISPOSE OF EXISTING MANMADE SURFACE FEATURES WITHIN THE LIMIT OF WORK INCLUDING BUILDINGS, STRUCTURES, PAVEMENTS, SLABS, CURBING, FENCES, UTILITY POLES, SIGNS, ETC. UNLESS INDICATED OTHERWISE ON THE DRAWINGS. REMOVE AND DISPOSE OF EXISTING UTILITIES, FOUNDATIONS AND UNSUITABLE MATERIAL BENEATH AND FOR A DISTANCE OF 10 FEET BEYOND THE PROPOSED BUILDING FOOTPRINT INCLUDING EXTERIOR COLUMNS.
2. EXISTING UTILITIES SHALL BE TERMINATED, UNLESS OTHERWISE NOTED. IN CONFORMANCE WITH THE CITY OF LOS ANGELES' STANDARD SPECIFICATIONS FOR UTILITIES, THE CONTRACTOR SHALL COORDINATE UTILITY SERVICE DISCONNECTS WITH THE UTILITY REPRESENTATIVES.
3. CONTRACTOR SHALL DISPOSE OF DEMOLITION DEBRIS IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS, ORDINANCES AND STATUTES.
4. THE DEMOLITION LIMITS DEPICTED IN THE PLANS IS INTENDED TO AID THE CONTRACTOR DURING THE BIDDING AND CONSTRUCTION PROCESS AND IS NOT INTENDED TO DEFINE EACH AND EVERY ELEMENT OF DEMOLITION. THE CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING THE DETAILED SCOPE OF DEMOLITION BEFORE SUBMITTING ITS BID/PROPOSAL TO PERFORM THE WORK AND SHALL MAKE NO CLAIMS AND SEEK NO ADDITIONAL COMPENSATION FOR CHANGED CONDITIONS OR UNFORESEEN OR UNKNOWN SITE CONDITIONS RELATED TO ANY CONDITIONS DISCOVERED DURING EXECUTION OF THE WORK.
5. UNLESS OTHERWISE SPECIFICALLY PROVIDED ON THE PLANS OR IN THE SPECIFICATIONS, THE ENGINEER HAS NOT PREPARED DESIGNS FOR AND SHALL HAVE NO RESPONSIBILITY FOR THE PRESENCE, DISCOVERY, REMOVAL, ABATEMENT OR DISPOSAL OF HAZARDOUS MATERIALS, TOXIC WASTES OR POLLUTANTS AT THE PROJECT SITE. THE ENGINEER SHALL NOT BE RESPONSIBLE FOR ANY CLAIMS OF LATE DELIVERY, DELAY, INJURY OR DEATH ARISING FROM THE PRESENCE OF HAZARDOUS MATERIALS AND CONTRACTOR SHALL INDEMNIFY AND HOLD HARMLESS THE ENGINEER FROM ANY CLAIMS MADE IN CONNECTION THEREWITH. MOREOVER, THE ENGINEER SHALL HAVE NO ADMINISTRATIVE OBLIGATIONS OF ANY TYPE WITH REGARD TO ANY CONTRACTOR AMENDMENT TO THE USE OF PRESENCE, DISCOVERY, REMOVAL, ABATEMENT OR DISPOSAL OF ASBESTOS OR OTHER HAZARDOUS MATERIALS.

Erosion Control

1. PRIOR TO STARTING ANY OTHER WORK ON THE SITE, THE CONTRACTOR SHALL NOTIFY APPROPRIATE AGENCIES AND SHALL INSTALL EROSION CONTROL MEASURES AS SHOWN ON THE PLANS AND AS IDENTIFIED IN FEDERAL, STATE, AND LOCAL APPROVAL DOCUMENTS PERTAINING TO THIS PROJECT.
2. CONTRACTOR SHALL INSPECT AND MAINTAIN EROSION CONTROL MEASURES ON A WEEKLY BASIS (MINIMUM) OR AS REQUIRED PER THE STORMWATER POLLUTION PREVENTION PLAN (SWPPP). THE CONTRACTOR SHALL ADDRESS DEFICIENCIES AND MAINTENANCE ITEMS WITHIN TWENTY-FOUR HOURS. THE CONTRACTOR SHALL INSPECT AND MAINTAIN EROSION CONTROL MEASUREMENTS SUCH THAT IT DOES NOT ENCUMBER OTHER DRAINAGE STRUCTURES AND PROTECTED AREAS.
3. CONTRACTOR SHALL BE FULLY RESPONSIBLE TO CONTROL CONSTRUCTION SUCH THAT SEDIMENTATION SHALL NOT AFFECT REGULATORY PROTECTED AREAS, WHETHER SUCH SEDIMENTATION IS CAUSED BY WATER, WIND, OR DIRECT DEPOSIT.
4. CONTRACTOR SHALL PERFORM CONSTRUCTION SEQUENCING SUCH THAT EARTH MATERIALS ARE EXPOSED FOR A MINIMUM OF TIME BEFORE THEY ARE COVERED, SEEDED, OR OTHERWISE STABILIZED TO PREVENT EROSION.
5. UPON COMPLETION OF CONSTRUCTION AND ESTABLISHMENT OF PERMANENT GROUND COVER, CONTRACTOR SHALL REMOVE AND DISPOSE OF EROSION CONTROL MEASURES AND CLEAN SEDIMENT AND DEBRIS FROM ENTIRE DRAINAGE AND SEWER SYSTEMS.

Existing Conditions Information

1. BASE PLAN: THE PROPERTY LINES SHOWN WERE DETERMINED BY AN ACTUAL FIELD SURVEY CONDUCTED BY STENBECK & TAYLOR, INC. PLAN # 738 OF 1981. THE TOPOGRAPH AND PHYSICAL FEATURES ARE BASED ON ACTUAL FIELD SURVEY PERFORMED ON THE GROUND BY STENBECK & TAYLOR, INC. DURING SEPTEMBER 2018.
2. GEOTECHNICAL DATA INCLUDING TEST PIT LOCATIONS WERE OBTAINED FROM SITE PLAN SHOWING PROPOSED REPLACEMENT SEWAGE SYSTEM PREPARED BY STENBECK & TAYLOR, INC DATED OCTOBER 12, 2010 AND FROM ADDITIONAL TESTING PERFORMED BY VHB IN NOVEMBER 2018.

Document Use

1. THESE PLANS AND CORRESPONDING CADD DOCUMENTS ARE INSTRUMENTS OF PROFESSIONAL SERVICE, AND SHALL NOT BE USED, IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS CREATED WITHOUT THE EXPRESSED, WRITTEN CONSENT OF VHB. ANY UNAUTHORIZED USE, REUSE, MODIFICATION OR ALTERATION, INCLUDING AUTOMATED CONVERSION OF THIS DOCUMENT SHALL BE AT THE USER'S SOLE RISK WITHOUT LIABILITY OR LEGAL EXPOSURE TO VHB.
2. CONTRACTOR SHALL NOT RELY SOLELY ON ELECTRONIC VERSIONS OF PLANS, SPECIFICATIONS, AND DATA FILES THAT ARE OBTAINED FROM THE DESIGNERS, BUT SHALL VERIFY LOCATION OF PROJECT FEATURES IN ACCORDANCE WITH THE PAPER COPIES OF THE PLANS AND SPECIFICATIONS THAT ARE SUPPLIED AS PART OF THE CONTRACT DOCUMENTS.
3. SYMBOLS AND LEGENDS OF PROJECT FEATURES ARE GRAPHIC REPRESENTATIONS AND ARE NOT NECESSARILY SCALED TO THEIR ACTUAL DIMENSIONS OR LOCATIONS ON THE DRAWINGS. THE CONTRACTOR SHALL REFER TO THE DETAIL SHEET DIMENSIONS, MANUFACTURERS' LITERATURE, SHOP DRAWINGS AND FIELD MEASUREMENTS OF SUPPLIED PRODUCTS FOR LAYOUT OF THE PROJECT FEATURES.

Proposed Urgent Care Facility

296 Old Oak Street
Pembroke, Massachusetts

[illegible]

Local Approvals

Nov. 15, 2018

Not Approved for Construction

Drawing Title

Legend and General Notes

Drawing Number

C-1

Sheet 1 of 9

Project Number
14239.00




11/19/2018



PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I, _____
TOWN CLERK OF THE TOWN OF PEMBROKE, MA
HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.



Proposed Urgent Care Facility

296 Old Oak Street
Pembroke, Massachusetts

No.	Revision	Date	Appvd.

Designed by	Checked by
AFG	KSS
Issued for	Date
	Nov. 15, 2018

Local Approvals

Not Approved for Construction

Drawing Title

Locus Map

Zoning District(S):	Business B District		
Overlay District(S):	Adult Use Overlay District		
Zoning Regulation Requirements	Existing	Required	Provided
MINIMUM LOT AREA	121,450 SF	80,000 SF	121,450 SF
FRONTAGE	404 Feet & 363 Feet ²	200 Feet	404 Feet & 363 Feet ²
MINIMUM LOT PERIMETER RATIO	83	44	83
FRONT YARD BUILDING SETBACK	53.7 Feet & 162 Feet	60 Feet ⁴	22.5 Feet & 17.5 Feet ⁷
FRONT YARD PARKING SETBACK	4.8 Feet & 17.3 Feet	60 Feet ⁴	4.8 Feet & 17.5 Feet
SIDE YARD BUILDING SETBACK	23.9 Feet & 54.5 Feet	30 Feet ⁴	23.9 Feet & 54.5 Feet
SIDE YARD PARKING SETBACK	11.4 Feet & 2.4 Feet	30 Feet ⁴	11.4 Feet & 5.0 Feet
REAR YARD BUILDING SETBACK	N/A ⁶	40 Feet ⁴	N/A ⁶
REAR YARD PARKING SETBACK	N/A ⁶	40 Feet ⁴	N/A ⁶
MINIMUM LOT WIDTH	205 Feet	135 Feet	205 Feet
MAXIMUM BUILDING HEIGHT	1 Story	3 Stories	2 Stories
MAXIMUM FLOOR AREA RATIO	17 %	35 %	21 %
MAXIMUM IMPERVIOUS	76 %	60 %	74 %
SITE LANDSCAPING - FRONT YARD	41 %	40 % ¹	40 %
SITE LANDSCAPING - SIDE YARD	49 %	40 % ¹	53 %
OPEN SPACE	24 %	25 % ²	26 %
INTERIOR PARKING LANDSCAPING	1 %	5 % ³	6 %

Project Number
14239.00



101 Walnut Street
PO Box 9151
Watertown, MA 02471
617.924.1770

PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I,
TOWN CLERK OF THE TOWN OF PEMBROKE, MA
HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.



0 10 20 40 Feet

Proposed Urgent Care
Facility

296 Old Oak Street
Pembroke, Massachusetts

No.	Revision	Date	Appvd.

Designed by AFG	Checked by KSS
Issued for	Date
Local Approvals	Nov. 15, 2018

Not Approved for Construction

Drawing Title

Grading, Drainage
& Erosion Control Plan



11/19/2018

C-4


Sheet 4 of 9

Project Number
14239.00

Notes

General

1. PROPOSED SHARED SYSTEM PER 310 CMR 15.100 THROUGH 15.293.
 - 1.1. EXISTING SOIL ABSORPTION SYSTEM (SAS) IS DESIGNED FOR 775 GALLONS/DAY. BOTTOM AREA = 1110 SF (37' LONG X 30' WIDE) AND IS A PRESSURE DOSE SYSTEM.
 - 1.1.1. EXISTING SOIL ABSORPTION SYSTEM (SAS) IS DESIGNED FOR 775 GALLONS/DAY. BOTTOM AREA = 1110 SF (37' LONG X 30' WIDE) AND IS A PRESSURE DOSE SYSTEM.
 - 1.2. PROPOSE TO EXPAND EXISTING LEACHING FIELD TO ACCOMMODATE PROPOSED BUILDING.
 - 1.2.1. PROPOSED ADDITIONAL FLOWS FOR 2-DOCTOR URGENT CARE FACILITY = 250 GALLONS/DAY PER DOCTOR X 2 DOCTORS = 500 GALLONS/DAY
 - 1.2.2. PROPOSED FIELD EXPANSION = 720 SF (24' X 30'). EXTEND EXISTING 7 LATERALS BY 24'



PEMBROKE PLANNING BOARD DEFINITIVE DEVELOPMENT PLAN APPROVALS			

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW


I,
TOWN CLERK OF THE TOWN OF PEMBROKE, MA
HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.

Proposed Urgent Care Facility
296 Old Oak Street
Pembroke, Massachusetts

No.	Revision	Date	Appvd.

Designed by AFG	Checked by KSS
Issued for	Date
Local Approvals	Nov. 15, 2018


Not Approved for Construction
Drawing Title
Utility Plan
Drawing Number



NOTES

1. ALL DIMENSIONS TO EDGES OF 4" PAVEMENT STRIPING.
2. 8' STALL WIDTH REFERS TO 8' CLEAR BETWEEN INSIDE EDGES OF PAVEMENT MARKINGS.
3. ALL SLOPES THROUGHOUT THE ACCESSIBLE PARKING AND AISLE AREAS SHALL NOT EXCEED 1.5%.
4. ACCESS AISLE MEASURED BETWEEN OUTSIDE EDGES OF PAVEMENT MARKINGS.


Accessible Parking Space 1/16
N.T.S. Source: VHB LD_552B



NOTES

1. THE MAXIMUM ALLOWABLE SIDEWALK AND CURB RAMP CROSS SLOPES SHALL BE 1.5 (1% MIN.).
2. THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE EXCLUDING CURB RAMP SHALL BE 5%.
3. THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE AT CURB RAMP SHALL BE 7.5%.
4. A MINIMUM OF 3 FEET CLEAR SHALL BE MAINTAINED AT ANY PERMANENT OBSTACLE IN ACCESSIBLE ROUTE (I.E., HYDRANTS, UTILITY POLES, TREE WELLS, SIGNS, ETC.).
5. CURB TREATMENT VARIES, SEE PLANS FOR CURB TYPE.
6. RAMP, CURB, AND ADJACENT PAVEMENTS SHALL BE GRADED TO PREVENT PONDING.
7. SEE TYPICAL SIDEWALK SECTION FOR RAMP CONSTRUCTION.
8. WHERE ACCESSIBLE ROUTES ARE LESS THAN 5' IN WIDTH (EXCLUDING CURBING) A 5' x 5' PASSING AREA SHALL BE PROVIDED AT INTERVALS NOT TO EXCEED 200 FEET.
9. ELIMINATE CURBING AT RAMP (OTHER THAN VERTICAL CURBING, WHICH SHALL BE SET FLUSH) WHERE IT ABUTS ROADWAY.
10. DETECTABLE WARNINGS SHALL CONTRAST VISUALLY WITH ADJOINING SURFACES.
11. DETECTABLE WARNINGS SHALL BE INSTALLED PERPENDICULAR TO ACCESSIBLE ROUTE.


Accessible Curb Ramp (ACR) Type 'A-D' 1/16
N.T.S. Source: VHB LD_500



NOTES

1. THE MAXIMUM ALLOWABLE SIDEWALK AND CURB RAMP CROSS SLOPES SHALL BE 1.5 (1% MIN.).
2. WHERE ACCESSIBLE ROUTE EXCLUDING CURB RAMP SHALL BE 5%.
3. THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE AT CURB RAMP SHALL BE 7.5%.
4. A MINIMUM OF 3 FEET CLEAR SHALL BE MAINTAINED AT ANY PERMANENT OBSTACLE IN ACCESSIBLE ROUTE (I.E., HYDRANTS, UTILITY POLES, TREE WELLS, SIGNS, ETC.).
5. CURB TREATMENT VARIES, SEE PLANS FOR CURB TYPE.
6. RAMP, CURB AND ADJACENT PAVEMENTS SHALL BE GRADED TO PREVENT PONDING.
7. SEE TYPICAL SIDEWALK SECTION FOR RAMP CONSTRUCTION.
8. WHERE ACCESSIBLE ROUTES ARE LESS THAN 5' IN WIDTH (EXCLUDING CURBING) A 5' x 5' PASSING AREA SHALL BE PROVIDED AT INTERVALS NOT TO EXCEED 200 FEET.
9. ELIMINATE CURBING AT RAMP WHERE IT ABUTS ROADWAY, EXCEPT WHERE VERTICAL CURBING IS INDICATED ON THE DRAWINGS TO BE INSTALLED AND SET FLUSH.
10. DETECTABLE WARNINGS SHALL CONTRAST VISUALLY WITH ADJOINING SURFACES.
11. DETECTABLE WARNINGS SHALL BE INSTALLED PERPENDICULAR TO THE ACCESSIBLE ROUTE.


Accessible Curb Ramp (ACR) Type 'D-D' 1/16
N.T.S. Source: VHB LD_503




NOTES

1. THE MAXIMUM ALLOWABLE SIDEWALK AND CURB RAMP CROSS SLOPES SHALL BE 1.5 (1% MIN.).
2. THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE EXCLUDING CURB RAMP SHALL BE 5%.
3. THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE AT CURB RAMP SHALL BE 7.5%.
4. A MINIMUM OF 3 FEET CLEAR SHALL BE MAINTAINED AT ANY PERMANENT OBSTACLE IN ACCESSIBLE ROUTE (I.E., HYDRANTS, UTILITY POLES, TREE WELLS, SIGNS, ETC.).
5. CURB TREATMENT VARIES, SEE PLANS FOR CURB TYPE.
6. RAMP, CURB AND ADJACENT PAVEMENTS SHALL BE GRADED TO PREVENT PONDING.
7. SEE TYPICAL SIDEWALK SECTION FOR RAMP CONSTRUCTION.
8. WHERE ACCESSIBLE ROUTES ARE LESS THAN 5' IN WIDTH (EXCLUDING CURBING) A 5' x 5' PASSING AREA SHALL BE PROVIDED AT INTERVALS NOT TO EXCEED 200 FEET.
9. ELIMINATE CURBING (OTHER THAN VERTICAL CURBING, WHICH SHALL BE SET FLUSH) WHERE IT ABUTS ROADWAYS.
10. DETECTABLE WARNINGS SHALL CONTRAST VISUALLY WITH ADJOINING SURFACES.
11. DETECTABLE WARNINGS SHALL BE INSTALLED PERPENDICULAR TO THE ACCESSIBLE ROUTE.


Accessible Curb Ramp (ACR) Type 'M-D' 1/16
N.T.S. Source: VHB LD_512




Bollard 1/16
N.T.S. Source: VHB LD_700



Bollard Mounted Sign 1/16
N.T.S. Source: VHB LD_703



HEAVY DUTY FLEXIBLE PAVEMENT




STANDARD DUTY FLEXIBLE PAVEMENT

NOTES

PAVEMENT SECTIONS ARE SUBJECT TO CHANGE AND WILL BE BASED ON THE RESULTS OF FURTHER GEOTECHNICAL INVESTIGATIONS.


Bituminous Concrete Pavement Sections 1/16
N.T.S. Source: VHB LD_430



NOTES

1. PROVIDE EXPANSION JOINTS
2. AT MIN. 30 FT. O.C. WITH PRE-FORMED JOINT FILLER.
3. PROVIDE TOOLED CONTROL JOINTS AT 6' O.C.
4. PROVIDE BROOM FINISH IN DIRECTION PERPENDICULAR TO CURB.


Concrete Sidewalk 1/16
N.T.S. Source: VHB LD_420




NOTES

1. CONCRETE FOR SIDEWALKS TO BE 4000 PSI AND FOR DRIVEWAYS 5000 PSI. BOTH MIXES TO BE TYPE II, 6% (1.5:1) AIR ENTRAINMENT.
2. PROVIDE EXPANSION JOINTS AT MIN. 30 FT. O.C. WITH PRE-FORMED EXPANSION JOINT FILLER & SEALER.
3. PROVIDE TOOLED CONTROL JOINTS AT 6' O.C.
4. PROVIDE BROOM FINISH IN DIRECTION PERPENDICULAR TO CURB.


Monolithic Concrete Curb (MCC) & Sidewalk 1/16
N.T.S. Source: VHB LD_421



Precast Concrete Curb (PCC) 1/16
N.T.S. Source: VHB LD_404




Vertical Granite Curb (VGC) 1/16
N.T.S. Source: VHB LD_402



NOTES

1. EXIT WIDTH SHALL BE A TWENTY-FIVE (25) FOOT MINIMUM, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS.
2. THE EXIT SHALL BE MAINTAINED IN A CONDITION WHICH SHALL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY. BERM SHALL BE PERMITTED. PERIODIC INSPECTION AND MAINTENANCE SHALL BE PROVIDED AS NEEDED.
3. STABILIZED CONSTRUCTION EXIT SHALL BE REMOVED PRIOR TO FINAL FINISH MATERIALS BEING INSTALLED.


Stabilized Construction Exit 1/16
N.T.S. Source: VHB LD_682



NOTES

1. STRAW WATTLE SHALL BE AS MANUFACTURED BY EARTHSAVER OR APPROVED EQUAL.
2. STRAW WATTLES SHALL OVERLAP A MINIMUM OF 12 INCHES.
3. STRAW WATTLE SHALL BE INSPECTED PERIODICALLY AND AFTER ALL STORM EVENTS, AND REPAIR OR REPLACEMENT SHALL BE PERFORMED PROMPTLY AS NEEDED.
4. TEMPORARY STRAW WATTLES TO BE REMOVED BY CONTRACTOR. ALL OTHERS TO REMAIN IN PLACE UNLESS DIRECTED OTHERWISE BY ENGINEER.
5. IF NON BIODEGRADABLE NETTING IS USED THE NETTING SHALL BE COLLECTED AND DISPOSED OF OFFSITE.

Straw Wattle - Erosion Control Barrier 1/16
N.T.S. Source: VHB LD_659



NOTES

1. INSTALL SILTSACK IN ALL CATCH BASINS WHERE INDICATED ON THE PLAN BEFORE COMMENCING WORK OR IN PAVED AREAS AFTER BINDER COURSE IS PLACED AND HAY BALES HAVE BEEN REMOVED.
2. GRATE TO BE PLACED OVER SILTSACK.
3. SILTSACK SHALL BE INSPECTED PERIODICALLY AND AFTER ALL STORM EVENTS AND CLEANING OR REPLACEMENT SHALL BE PERFORMED PROMPTLY AS NEEDED. MAINTAIN UNTIL UPSTREAM AREAS HAVE BEEN PERMANENTLY STABILIZED.

Siltsack Sediment Trap 1/16
N.T.S. Source: VHB LD_674



PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

No.	Revision	Date	Appr.

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I, _____
TOWN CLERK OF THE TOWN OF PEMBROKE, MA
HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.

Proposed Urgent Care
Facility

296 Old Oak Street
Pembroke, Massachusetts


No.	Revision	Date	Appr.

Designed by AFG Checked by KSS

Local Approvals Nov. 15, 2018

Not Approved for Construction

Site Details 1



C-6.1







Sheet 6 of 9

11/19/2018

Project Number
14239.00



101 Walnut Street
PO Box 9151
Watertown, MA 02471
617.924.1770



PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT NECESSARILY INDICATE COMPLIANCE WITH THE PEMBROKE ZONING BY-LAW

I, TOWN CLERK OF THE TOWN OF PEMBROKE, MA HEREBY CERTIFY THAT THE NOTICE OF APPROVAL OF THIS PLAN BY THE PLANNING BOARD HAS BEEN RECEIVED AND RECORDED AT THIS OFFICE AND NO APPEAL WAS RECEIVED DURING THE NEXT TWENTY DAYS AFTER RECEIPT AND RECORDING OF SAID NOTICE.

Proposed Urgent Care Facility

296 Old Oak Street
Pembroke, Massachusetts

No.	Revision	Date	Appr.

Designed by AFG

Checked by KSS

Issued for Local Approvals


Nov. 15, 2018

Not Approved for Construction

Site Details 2

C-6.2

11/19/2018





101 Walnut Street
PO Box 9151
Watertown, MA 02471
617.924.1770

Tree Protection

- EXISTING TREES TO REMAIN SHALL BE PROTECTED WITH TEMPORARY CONSTRUCTION FENCE. ERECT FENCE AT EDGE OF THE TREE DRILIPE PRIOR TO START OF CONSTRUCTION.
- CONTRACTOR SHALL NOT OPERATE VEHICLES WITHIN THE TREE PROTECTION AREA. CONTRACTOR SHALL NOT STORE VEHICLES OR MATERIALS, OR DISPOSE OF ANY WASTE MATERIALS, WITHIN THE TREE PROTECTION AREA.
- DAMAGE TO EXISTING TREES CAUSED BY THE CONTRACTOR SHALL BE REPAIRED BY A CERTIFIED ARBORIST AT THE CONTRACTOR'S EXPENSE.

Plant Maintenance Notes

- CONTRACTOR SHALL PROVIDE COMPLETE MAINTENANCE OF THE LAWN AND PLANTINGS. NO IRRIGATION IS PROPOSED FOR THIS SITE. THE CONTRACTOR SHALL SUPPLY SUPPLEMENTAL WATERING FOR NEW LAWN AND PLANTINGS DURING THE ONE YEAR PLANT GUARANTEE PERIOD.
- CONTRACTOR SHALL PROVIDE ALL MATERIALS, LABOR, AND EQUIPMENT FOR THE COMPLETE LANDSCAPE MAINTENANCE WORK. WATER SHALL BE PROVIDED BY THE CONTRACTOR.
- WATERING SHALL BE REQUIRED DURING THE GROWING SEASON, WHEN NATURAL RAINFALL IS BELOW ONE INCH PER WEEK.
- WATER SHALL BE APPLIED IN SUFFICIENT QUANTITY TO THOROUGHLY SATURATE THE SOIL IN THE ROOT ZONE OF EACH PLANT.
- CONTRACTOR SHALL REPLACE DEAD OR DYING PLANTS AT THE END OF THE ONE YEAR GUARANTEE PERIOD. CONTRACTOR SHALL TURN OVER MAINTENANCE TO THE FACILITY MAINTENANCE STAFF AT THAT TIME.

Planting Notes


- ALL PROPOSED PLANTING LOCATIONS SHALL BE STAKED AS SHOWN ON THE PLANS FOR FIELD REVIEW AND APPROVAL BY THE LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- CONTRACTOR SHALL VERIFY LOCATIONS OF ALL BELOW GRADE AND ABOVE GROUND UTILITIES AND NOTIFY OWNERS REPRESENTATIVE OF CONFLICTS.
- NO PLANT MATERIALS SHALL BE INSTALLED UNTIL ALL GRADING AND CONSTRUCTION HAS BEEN COMPLETED IN THE IMMEDIATE AREA. CONTRACTOR SHALL NOTIFY OWNER'S REPRESENTATIVE OF ANY CONFLICT.
- A 3-INCH DEEP MULCH PER SPECIFICATION SHALL BE INSTALLED UNDER ALL TREES AND SHRUBS, AND IN ALL PLANTING BEDS, UNLESS OTHERWISE INDICATED ON THE PLANS, OR AS DIRECTED BY OWNER'S REPRESENTATIVE.
- ALL TREES SHALL BE BALLED AND BURLAPPED, UNLESS OTHERWISE NOTED IN THE DRAWINGS OR SPECIFICATION, OR APPROVED BY THE OWNER'S REPRESENTATIVE.
- FINAL QUANTITY FOR EACH PLANT TYPE SHALL BE AS GRAPHICALLY SHOWN ON THE PLAN. THIS NUMBER SHALL TAKE PRECEDENCE IN CASE OF ANY DISCREPANCY BETWEEN QUANTITIES SHOWN ON THE PLANT LIST AND ON THE PLAN. THE CONTRACTOR SHALL REPORT ANY DISCREPANCIES BETWEEN THE NUMBER OF PLANTS SHOWN ON THE PLANT LIST AND PLANT LABELS PRIOR TO BIDDING.
- ANY PROPOSED PLANT SUBSTITUTIONS MUST BE REVIEWED BY LANDSCAPE ARCHITECT AND APPROVED IN WRITING BY THE OWNER'S REPRESENTATIVE.
- ALL PLANT MATERIALS INSTALLED SHALL MEET THE SPECIFICATIONS OF THE "AMERICAN STANDARDS FOR NURSERY STOCK" BY THE AMERICAN ASSOCIATION OF NURSERYMEN AND CONTRACT DOCUMENTS.
- ALL PLANT MATERIALS SHALL BE GUARANTEED FOR ONE YEAR FOLLOWING DATE OF FINAL ACCEPTANCE.
- AREAS DESIGNATED "LOAM & SEED" SHALL RECEIVE MINIMUM 6" OF LOAM AND SPECIFIED SEED MIX. LAWNS OVER 2:1 SLOPE SHALL BE PROTECTED WITH EROSION CONTROL FABRIC.
- ALL DISTURBED AREAS NOT OTHERWISE NOTED ON CONTRACT DOCUMENTS SHALL BE LOAM AND SEEDED OR MULCHED AS DIRECTED BY OWNER'S REPRESENTATIVE.
- THIS PLAN IS INTENDED FOR PLANTING PURPOSES. REFER TO SITE / CIVIL DRAWINGS FOR ALL OTHER SITE CONSTRUCTION INFORMATION.

PLANT SCHEDULE

DECIDUOUS TREES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
AR	9	Acer rubrum 'Redpointe'	Redpointe Maple	4" CAL.
BN	5	Betula nigra 'Heritage'	Multi-Stem Heritage River Birch	10 - 12" HT.
GT	3	Gleditsia triacanthos 'Skyline'	Skyline Honeylocust	4" CAL.
QC	15	Quercus coccinea	Scarlet Oak	4" CAL.
SHRUBS	QTY	BOTANICAL NAME	COMMON NAME	SIZE
FG	7	Fothergilla gardenii	Dwarf Fothergilla	18 - 24" HT.
JC	14	Juniperus conferta	Shore Juniper	18 - 24" SPD
RP	17	Rhododendron x 'PJM'	PJM Rhododendron	2 - 2 1/2" HT.
RG	86	Rhus aromatica 'Gro-Low'	Gro-Low Fragrant Sumac	18 - 24" SPD
SLP	18	Spiraea japonica 'Little Princess'	Little Princess Japanese Spirea	18 - 24" SPD
VN	17	Viburnum nudum 'Winterthur'	Smooth Witherod	2 - 2 1/2" HT.
GRASSES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
CKF	21	Calamagrostis x acutiflora 'Karl Foerster'	Karl Foerster Feather Reed Grass	2 GAL.
PERENNIALS	QTY	BOTANICAL NAME	COMMON NAME	SIZE
HHR	110	Hemerocallis x 'Happy Returns'	Happy Returns Daylily	1 GAL.
HSO	21	Hemerocallis x 'Stella de Oro'	Stella de Oro Daylily	1 GAL.

SPACING
30" o.c.

SPACING
24" o.c.



PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I, TOWN CLERK OF THE TOWN OF PEMBROKE,
MA HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.

Proposed Urgent Care
Facility

296 Old Oak Street
Pembroke, Massachusetts

No.	Revision	Date	Apprv.

Designed by	Checked by
Issued for	Date
Local Approvals	Nov. 15, 2018

Not Approved for Construction

Planting Plan


Drawing Title	Drawing Number




L-1

Sheet 8 of 9

Project Number
14239.00



Multistem Tree Planting 1/16
N.T.S. Source: VHB LD_606



Tree Planting 9/18
N.T.S. Source: VHB LD_602

PEMBROKE PLANNING BOARD
DEFINITIVE DEVELOPMENT PLAN APPROVALS

THIS SITE PLAN APPROVAL DOES NOT
NECESSARILY INDICATE COMPLIANCE WITH THE
PEMBROKE ZONING BY-LAW

I, TOWN CLERK OF THE TOWN OF PEMBROKE,
MA HEREBY CERTIFY THAT THE NOTICE OF
APPROVAL OF THIS PLAN BY THE PLANNING
BOARD HAS BEEN RECEIVED AND RECORDED AT
THIS OFFICE AND NO APPEAL WAS RECEIVED
DURING THE NEXT TWENTY DAYS AFTER
RECEIPT AND RECORDING OF SAID NOTICE.

Proposed Urgent Care
Facility

296 Old Oak Street
Pembroke, Massachusetts


No.	Revision	Date	Appr.

Designed by	Checked by


Issued for	Date
Local Approvals	Nov. 15, 2018

Not Approved for Construction

Landscape Details




Perennial and Ornamental Grass Planting 1/16
N.T.S. Source: VHB LD_618



- NOTES
1. LOOSEN ROOTS AT THE OUTER EDGE
OF ROOTBALL OF CONTAINER
GROWN SHRUBS.


Shrub Bed Planting 1/16
N.T.S. Source: VHB LD_601





Drawn For : VHB


EXISTING CONDITIONS PLAN
296 OLD OAK STREET
PARCEL G15-35
PEMBROKE, MA



Drawn By : CT
Checked By : BJT
Scale : 1" = 30'
Date : 11-14-18
Job No. : 8617
Plan No: 8617-Exist Cond

STENBECK & TAYLOR, INC.
Registered Professional Engineers and Land Surveyors
Since 1951
844 Webster Street
Suite 3
Marshfield, Ma. 02050
781-834-8591
Fax: 781-837-8238
www.stenbeckandaylor.com

\\dms\activeprojects\CMD Pembroke MA\CMD Pembroke MA_Shell_V20.dwg Tuesday, September 11, 2018 2:10 PM



Building A Floor Plan
SCALE: 1/4" = 1'-0"

ConvenientMD Building Shell
296 Old Oak Street
Pembroke, MA 02359

DENNIS MILES, P.A.
THE ARCHITECTS
697 Union Street, Manchester, NH
603-425-5068 FAX 603-425-1067

This plan is a copy of the original drawing and is not to be used for construction without the written consent of the architect. The architect is not responsible for the accuracy of the information contained herein, and the recipient agrees to release the architect from any liability for errors or omissions. The architect is not responsible for the accuracy of the information contained herein, and the recipient agrees to release the architect from any liability for errors or omissions.

**Building Shell
Floor Plan**

revisions:

date: 9/11/18
proj. no.:

A101

\\Volumes\Active\Projects\ConvenientMD Urgent Care (All Active Locations)\CMD Pembroke MA\CMD Pembroke Shell - 2018022018025_Convenient_MD_PembrokeMA_Shell_V20.dgn Tuesday, November 13, 2018



1 North Elevation (Church Street)
SCALE: 1/8" = 1'-0"



2 South Elevation (Route 3)
SCALE: 1/8" = 1'-0"



3 East Elevation (Old Oak Street)
SCALE: 1/8" = 1'-0"



4 West Elevation (Parking)
SCALE: 1/8" = 1'-0"

CONVENIENTMD EXTERIOR FINISH NOTES:

Pitched Roofs & Canopies: Standing Seam Metal Roofing, Pac-Clad "Snap Clad" or approved equal, Color to match Englert Colonial Red or architect approved equal

Membrane Roof: Fully Adhered White .060 TPO Membrane on coverboard over R30 min XPS rigid insulation,

Eave & Canopy Soffits: Pac Clad Aluminum Flush Soffit Panels or approved equal. Upper tower soffit color to match roof color. Lower canopy soffits to be white.

Exterior Clapboard Siding: Pre-Finished James Hardie clapboard siding, 4" exposure. Color TBD

Cultured Stone: Cultured Stone "Suede Drystack Ledgestone Cultured Stone CSV-2010"

Aluminum Storefront: All Aluminum Storefront doors/windows shall be Efco Series 403 Thermally Broken aluminum storefront system or approved equal.

Two sets of glass exterior double doors with thermally broken aluminum frames with two ADA automatic door openers.
Color to be white

Rear Exit Door: Insulated Hollow Metal rear door with ADA push exit hardware, electric strike & FOB access control system.

Envelope Insulation:

- Low slope roof to be R30 min continuous between exterior insulated walls, ensuring continuity of all envelope insulation.
- Exterior Walls to be R21 (3") min Closed cell spray in place polyurethane insulation in stud cavity & 1" min exterior continuous insulation to outside face of wall sheathing.
- 2" min rigid insulation from top of foundation footing to top of slab elevation on outside face of foundation wall, Reinforced Stucco finish over exposed foundation insulation.

Exterior Lighting:

- Provide & Install recessed LED lighting fixtures in all canopies, overhangs at both 10'-0" AFF canopies/overhangs and upper tower overhang.
- Provide & Install Square recessed LED down lights around perimeter of upper & lower canopy/roof overhangs
- Provide additional Linear LED wall wash down lights to graze down corner columns of tower.
- Provide LED Wall pack lighting at rear doors
- Provide Linear LED lighting above tower canopies per electrical drawings.

ConvenientMD Building Shell
296 Old Oak Street
Pembroke, MA 02359

DENNIS MIRE, P.A.
THE ARCHITECTS
697 Union Street, Manchester, NH
603-625-4548 FAX 603-625-1067

The material contained in these drawings and the design they represent are the exclusive property of Dennis M. Mires, P.A. and are not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without written permission of Dennis M. Mires, P.A.

Elevations

revisions:

date: 11/13/18

proj. no.:

A201


Project:

URGENT
CARE
PEMBROKE,
MA

Notes:

FILE:
urgentcare.agi

Date:
11-20-18



- DUE TO CHANGING LIGHTING ORDINANCES IT IS THE CONTRACTORS RESPONSIBILITY TO SUBMIT THE SITE PHOTOMETRICS AND LUMINAIRE SPECS TO THE LOCAL INSPECTOR BEFORE ORDERING TO ENSURE THIS PLAN COMPLIES WITH LOCAL LIGHTING ORDINACES.

- THIS LIGHTING DESIGN IS BASED ON INFORMATION SUPPLIED BY OTHERS. CHANGES IN ELECTRICAL SUPPLY, AREA GEOMETRY AND OBJECTS WITHIN THE LIGHTED AREA MAY PRODUCE ILLUMINATION VALUES DIFFERENT FROM THE PREDICTED RESULTS SHOWN ON THIS LAYOUT.

- THIS LAYOUT IS BASED ON .IES FILES THAT WERE LAB TESTED OR COMPUTER GENERATED. ACTUAL RESULTS MAY VARY.

Luminaire Schedule						
Symbol	Qty	Label	Lumens/Lamp	Arrangement	LLF	Description
	3	A	N.A.	SINGLE	0.900	LSMT-4-C-M-TSW-D-FOUR BRICK TYPE 5 1050MA LED
	6	B	N.A.	SINGLE	0.900	LSMT-2-C-M-T3-D-TWO BRICK TYPE 3 1050MA LED


Calculation Summary								
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min	
SITE	Illuminance	Fc	1.35	5.6	0.0	N.A.	N.A.	
PARKING AND DRIVE	Illuminance	Fc	3.29	5.6	1.5	2.19	3.73	

Luminaire Location Summary			
LumNo	Label	Z-luminaire height	Tilt
1	A	25	0
2	A	25	0
3	A	25	0
4	B	25	0
5	B	25	0
6	B	25	0
7	B	25	0
8	B	25	0
9	B	25	0

Notes:

1. Calculation at grade.

2. Based on 25' AFG fixture mounting height.




LSMT High Lumen Output Scimitar LED Area Light

PHOTOMETRICS

IES INDOOR REPORT
PHOTOMETRIC FILE
NAME: LSMTSCMT5WD

Type V Narrow Optical
Assembly
8 Brick, 1050mA, Cool
White


864W LSMT LED Scimitar
Color Temperature: 5,000 K



IES INDOOR REPORT
PHOTOMETRIC FILE
NAME: LSMTSCMT5WD

Type V Wide Optical
Assembly
8 Brick, 1050mA, Cool
White

864W LSMT LED Scimitar
Color Temperature: 5,000 K



LUMINAIRE CHARACTERISTICS

1050 mA Drive Current												
# of LED Bricks	Drive Current	Color Temp	Delivered Lumens								System Wattage	L70 @ 25°C
			TYPE II	TYPE III	TYPE IV	TYPE 4A	TYPE 4T	FAW	TYPE 5N	TYPE 5M	TYPE 5W	
1 BRICK	1050 mA	Cool White (5000K)	11310	11540	11550	11950	11410	12370	11110	11825	11880	108
2 BRICK	1050 mA	Cool White (5000K)	22620	23080	23100	23900	22820	24740	22220	23650	23760	216
4 BRICK	1050 mA	Cool White (5000K)	45240	46160	46200	47800	45640	49480	44440	47300	47520	432
6 BRICK	1050 mA	Cool White (5000K)	67860	69240	69300	71700	68460	74220	66660	70950	71280	648
8 BRICK	1050 mA	Cool White (5000K)	90480	92320	92400	95600	91280	98960	88880	94600	95040	864
1 BRICK	1050 mA	Neutral White (4100K)	10875	11096	11106	11490	10971	11894	10683	11370	11423	108
2 BRICK	1050 mA	Neutral White (4100K)	21750	22192	22212	22981	21942	23788	21365	22740	22846	216
4 BRICK	1050 mA	Neutral White (4100K)	43500	44385	44423	45962	43885	47577	42731	45481	45692	432
6 BRICK	1050 mA	Neutral White (4100K)	65250	66577	66635	68942	65827	71365	64096	68221	68538	648
8 BRICK	1050 mA	Neutral White (4100K)	87000	88770	88846	91924	87770	95154	85461	90961	91384	864

WARNING: This fixture was designed for down aiming and must be used in a manner that prevents the fixture from tilting at an angle greater than 45 degrees. Failure to do so will void the warranty. For flood light applications please see the LSMA Scimitar LED Flood Light.



2707 SATSUMA | DR. DALLAS, TX 75229 | PH: 800.225.0727 | FX: 214.350.0591 | www.techlightusa.com

All dimensions and specifications are subject to change without notice.

REV: 20170803-01


LSMT High Lumen Output Scimitar LED Area Light

AVAILABLE FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting options must be ordered separately.



Dimensions shown for 6 Brick Unit



Dimensions shown for 4 Brick Unit

FIXTURE & MOUNTING ACCESSORIES

S213*
Angled Back Light Shield



PCR7
7-Pin Twist-Lock Photocell Receptacle ANSI C136-41 and Receptacle Shoring Cap



PC2
48V Twist-Lock Photocell



PC5
Multi-Tap (105-285V) Twist-Lock Photocell



SDARM, SDARM-R
Die Cast Decorative Arm Mount



QMSCM*
Quick Mount with 8" SSA-M Straight Arm (4 Brick Max)



NOTES

1 EPA's shown include both the fixture and the mounting apparatus.
2 QMSCM Quick Mount only available for fixtures with up to 4 bricks.
3 Order one per LED brick. Field installed.

EPA RATINGS (ft²)

Fixture Configuration	ARM MOUNT		
	1 or 2 Brick EPA's	4 Brick EPA's	6 Brick EPA's
1 or 2 Brick	1.0	1.3	1.6
4 Brick	2.0	2.6	3.2
6 Brick	1.9	2.4	3.0
8 Brick	2.5	3.3	4.0
4 or 6 or 8 Brick	3.5	4.5	5.5

Fixture Configuration	FIXTURE WEIGHTS (APPROX.)		
	1 or 2 Brick	4 Brick	6 Brick
Weight (lbs)	23 lbs	35 lbs	47 lbs

www.techlightusa.com

All dimensions and specifications are subject to change without notice.

REV: 20170803-01



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The high lumen output luminaire is designed to be a replacement for HD fixtures up to 1000W. It is optimal for lighting applications where long life, low maintenance, and consistent color rendering is required. Areas with limited accessibility due to fixture location or where heavy pedestrian or vehicle traffic makes maintenance difficult are ideal applications. The high wattage/lumen output allows the fixture to be used for parking, restaurant, quick service, shopping centers or sports lighting applications.

CONSTRUCTION — The heavy duty housing is constructed of cast aluminum with heat dissipating fins. The optical assemblies are sealed in place using a silicone gasket for weather tight protection. Modular LED system for ease of maintenance. ETL listed for wet locations (IP64). Additional IP66 rating available upon request. Each fixture comes standard with preps to accommodate advanced wireless control, management and reporting systems for outdoor lighting.

FINISH — A corrosion-resistant black E-Coat layer that forms a uniform and all-encompassing protective barrier is applied to the fixtures prior to electrostatically applying a super durable powder coat finish. Standard colors available: Black, Bronze, US Green, US White. Custom colors available upon request.

OPTICAL SYSTEM — Made with a state of the art UV stabilized acrylic high performance refractive optical assemblies that use high transmissivity materials to achieve precise photometric distributions. Available in Type II, III, IV, IV Automotive, Automotive Frontline Wide, IV Tennis, V Narrow, V Medium and V Wide beam configurations. Optics may be ordered rotated 90 degrees for perimeter lighting or walkway applications (optics are not field rotatable). The full cutoff fixture is Star Light Friendly (meets or exceeds Dark Sky requirements) in the horizontal position.

ELECTRICAL SYSTEM — Available in up to a 8 brick LED system in 5000K/70 CRI Cool White (+/- 50K) or 4100K/70 CRI Neutral White color temperatures propagated with Philips Lumileds Luxeon MK LEDs. Consult factory for high CRI (90+) model availability. Available with 100-300V 50/60 Hz Cages.

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

LSMT	# OF LED'S	COLOR TEMP	# LED'S PER BRICK	OPTICS	DRIVE CURRENT	VOLTAGE	OPTIONS	FINISH
TYPE B	1 = Type I	1 = Cool White (5000K)	M = 8 Luxeon MK LEDs	T2 = Type II	D = 1050 mA	1 = Multi-Tap	L = Left Rotated Optics	BZ = Bronze
TYPE A	2 = 2 Brick	N = Neutral White (4100K)		T3 = Type III	2 = 34V-480V		R = Right Rotated Optics	BK = Black
	4 = 4 Brick			T4 = Type IV			R = Right Rotated Optics	GR = US Green
	6 = 6 Brick			T5 = Type V Auto			R = Right Rotated Optics	WH = White
				FAW = Frontline Auto Wide			R = Right Rotated Optics	SP = Special
				T6 = Type V Narrow				
				T7 = Type V Medium				
				T8 = Type V Wide				

ACCESSORIES

(Order as separate line items)

SDARM Die Cast Decorative Arm Mount (Square Pole, 1.4 EPA)

SDARM-R Die Cast Decorative Arm Mount (Round Pole, 1.4 EPA)

QMSCM* Quick Mount with 8" SSA-M Straight Arm (4 Brick Max)

S213* Angled Back Light Shield

PCR7* 7-Pin Twist-Lock Photocell Receptacle ANSI C136-41 and Receptacle Shoring Cap

PC2 48V Twist-Lock Photocell

PC5 Multi-Tap (105-285V) Twist-Lock Photocell

IP66* Additional IP66 Fixture Rating

NOTES

1 = Multi-Volt is an auto ranging power supply from 100V to 300V input.

2 = Custom RAL color matching is available. Contact your sales representative for additional info.

3 = QMSCM Quick Mount only available for fixtures with up to 4 bricks.

4 = Order one per LED brick. Field installed.

5 = Photocell Receptacle must be installed at the factory. No field installation.

6 = Additional IP66 rating may not be charged once production has begun on the fixtures.

DesignLights Consortium® Qualified. Please go to www.designlights.org for the current Qualified Products List. Further details about qualified models may be found under Family Models.



www.techlightusa.com

All dimensions and specifications are subject to change without notice.

REV: 20170803-01

TECHLIGHT

2707 SATSUMA

DALLAS, TX
75229

Project:

URGENT
CARE
PEMBROKE,
MA

Notes:

FILE:

urgentcare.agi

Date:

11-20-18